

Easy locker: Serratura **RFID**

Material: ABS+Zinc alloy

Size: Lock body(L*W*H): 80*80*27mm;

Lock hook(L*W*H):75*27*21.5mm

Weight: 200g(with lock hook)

Battery: DC 6V (4*1.5VAAA)

Driven mode: Motor/servo

Power consumption: Static 70uA; Dynamic 200 mA

Warning voltage: 4.5 V

Unlock way: RFID card/ 13.56Mhz

Response time: Less than 500ms

Working temperature: -25°C ~ +55°C

Working humidity:5% ~ 95%RH

Working life:1 year

Salt spray testing: 72 hours

Application: Dormitory storage locker; Gym cabinet; Swimming pool storage locker; Drawer



SMART RFID CABINET LOCK

ABS shell with pearl chrome plated

Use PCB+reader chip,
more stable and longer
reading distance



Emergency power supply

Acrylic screen+protective slim,
high sensitive touch keypad

Micro USB connector
for power supply
3.5mm socket



Use connectors rather than soldering
for connection

Special design easy to lock-in,
high tolerance of installation

Pushing bars with spring,
help to push door open



Casting stainless steel pin holder.
Excellent anti-force
performance: 150kgs



Nickel plated screws

EASY LOCKER

- **NESSUN PC ALL'INTERNO DELLA STRUTTURA**

Serratura autonoma nessuna key pre impostata, riapre con la stessa card con cui chiude.

- **NESSUN INCONVENIENTE DOVUTO ALLA GESTIONE DEI DATI**

Dopo l'apertura la serratura ritorna libera e nuovamente riutilizzabile dall'utente successivo.

- **EASY REPLACE**

Può sostituire qualsiasi blocchetto ed è premunita di sistema di sblocco con pacco batteria esterno in caso di esaurimento batterie.

SERRATURA RFID PER CASSETTI ED ARMADIETTI

EASY LOCKER

Serratura RFID per armadietti e cassetti,

Nessun software necessario

Possibilità di innestare connettore per alimentazione esterna in caso di esaurimento batterie.

Durata batterie +/- 2 anni

Nessuna manutenzione ed adattabile a qualsiasi armadietto.

Livelli utente e Master card

Caratteristiche tecniche Serratura:

Alimentazione: DC 6V

Consumo: 0,04 A 0,12W

Dimensioni parte esterna: LxHxP

80x80x27mm

Dimensioni parte Interna: LxHxP

75x27x21.5mm

Time life: 145K ore

